

AIRDOR® Blade



Model	EL1500		EL2000		EL2500	
Speed	High	Low	High	Low	High	Low
Air volume (m3/s)	0.63	0.43	0.84	0.57	1.05	0.71
Heat capacity LPHW (kW) (82/71/15°C)	17.8	12.2	23.7	16.1	29.7	20.1
LPHW connection size	1"					
LPHW flowrate (litres/s)	0.39	0.26	0.51	0.35	0.64	0.44
LPHW water pressure drop (kPa)	3.5	1.6	6.5	3.1	10.7	5.0
Electric heating capacity (kW)	18		21		27	
Fan running current (A)	2.5		4.0		4.5	
Approximate noise level dBA @ 3m	60	54	62	56	63	57

Type	Hot water			Electric			Ambient		
Model	EL1500W	EL2000W	EL2500W	EL1500E	EL2000E	EL2500E	EL1500A	EL2000A	EL2500A
Weight (kg)	76	104	125	74	101	121	66	90	108
Width (mm)	1500	2000	2500	1500	2000	2500	1500	2000	2500
Depth (mm)	750	750	750	750	750	750	750	750	750
Height (mm)	400	400	400	400	400	400	400	400	400

- Designer door curtain for overdoor mounting in distinctive oval shape.
- Suitable for mounting heights of up to 3.5m.
- Casing from galvanised sheet powder coated white to RAL9010 as standard (other RAL colours available) with option for brushed stainless steel.
- Linear discharge grille on bottom of unit, return air grille on top of unit.
- Suitable for wall mounting or ceiling mounting and supplied with hollow pipe suspensions and fixing flanges.
- Units available with LPHW heating coils, electric heating elements or as ambient units with no air treatment.
- LPHW and ambient units available with on/off and change speed remote switching.
- Electric heat units available with remote on/off, change speed and heat setting switches.
- Advanced electronic controller available for timed unit control, master slave arrangements, BMS switching and thermostat control.
- Hot water and ambient units use a 230V/1ph/50Hz supply, electric units use a 400V/3ph/50Hz supply