



'THE' NAME IN MIDDLE EAST DEHUMIDIFICATION



T Z 川 刀 い

SPC HIDROS > General Range

DH

The SPC HIDROS General Range offers a comprehensive selection of robust, compact and versatile dehumidifier units. A wide range of capacities makes these units suitable for large and small applications.

-	
MODEL	CAPACITY (I/24h)
DH75	75
DH100	94
DH120	124
DH130	129
DH160	164
DH200	194

CAPACITY (I/24h)
330
415
564
738
937



DHH

Horizontal outlet dehumidifiers for general use. A variable outlet grille position allows for side or top outlet options.

MODEL	CAPACITY (I/24h)
DHH75	75
DHH100	94
DHH120	124





DHZ

Dehumidifiers for general applications with remote condenser for temperature control.

MODEL	CAPACITY (I/24h)
DHZ200	194
DHZ330	330
DHZ400	415

MODEL	CAPACITY (I/24h)
DHZ560	564
DHZ740	738
DHZ940	937

All units in the GENERAL RANGE are rated at 30°C ambient temperature and 80% relative humidity

SPC HIDROS > High Ambient Temperature Units

HH-HHZ

SPC HIDROS High Ambient Temperature dehumidifiers are industrial style units designed for use in temperatures up to 60°C. The High Ambient Temperature range is available with a remote condenser for temperature control (HHZ).

MODEL	CAPACITY (I/24h)
HH500	523
HH700	718
HH1500	1451

MODEL	CAPACITY (I/24h)
HHZ500	523
HHZ700	718
HHZ1500	1451



All HIGH AMBIENT TEMPERATURE UNITS are rated at 40°C ambient temperature and 40% relative humidity



SPC HIDROS > Cold Room Units

CH & CHZ



SPC HIDROS Cold Room Units are industrial dehumidifiers for cold room applications. The full range is available with a remote condenser for temperature control (CHZ).

MODEL	CAPACITY (I/24h)
CH85	84
CH150	156
CH180	186
CH250	245
CH320	314
CH400	402

MODEL	CAPACITY (I/24h)
CHZ85	84
CHZ150	156
CHZ180	186
CHZ250	245
CHZ320	314
CHZ400	402

All COLD ROOM UNITS are rated at 15°C ambient temperature and 80% relative humidity

SPC HIDROS > Swimming Pool Range







SCH

SPC HIDROS SCH is a wall mounted range of swimming pool dehumidifiers. Designed to provide low noise dehumidification within a compact shell, the SCH is the perfect solution for smaller swimming pool applications.

MODEL	CAPACITY (I/24h)
SCH50	57
SCH75	75
SCH100	94
SCH120	124

SDH

The SPC HIDROS SDH model is available in a wide range of capacities. The units are designed for use in medium and large-sized swimming pool applications and are suitable for plant room installation. Their compact design ensures that the SDH range saves space without compromising performance.

MODEL	CAPACITY (I/24h)
SDH100	94
SDH120	124
SDH160	164
SDH200	194
SDH330	330

MODEL	CAPACITY (I/24h)
SDH400	415
SDH560	564
SDH740	738
SDH940	937
SDH1100	1130

MODEL	CAPACITY (I/24h)
SDH1300	1280
SDH1500	1490
SDH1800	1880
SDH2200	2310
SDH3000	3050

SMD

The SPC HIDROS SMD model is a unique dehumidifer design that incorporates heat pipe technology to increase the rate of moisture removal. This technologically advanced design is housed in a robust and compact case, offering the most energy efficient dehumidification available.

MODEL	CAPACITY (I/24h)
SMD160	160
SMD300	300

All units in the SWIMMING POOL RANGE are rated at 30°C ambient temperature and 80% relative humidity





SPC Heat Pipes (FZC) P.O. BOX 9532, Sharjah, United Arab Emirates

Dubai Office PO BOX 50816, Dubai, United Arab Emirates

Tel: 00 9714 334 1178 Fax: 00 9714 334 1179 E-mail: spc-hidros@spcoils.ae Web: www.spcoils.ae





All SPC HIDROS Dehumidifiers are of European manufacture.

S P C Heat Pipes (FZC) reserves the right to amend the specification whilst pursuing a policy of continuous improvement in performance and design